- (e) The individual in charge of the organizational unit that has been delegated the responsibilities for bridge inspection, reporting and inventory shall determine and designate on the individual inspection and inventory records and maintain a master list of the following:
- (1) Those bridges which contain fracture critical members, the location and description of such members on the bridge and the inspection frequency and procedures for inspection of such members. (Fracture critical members are tension members of a bridge whose failure will probably cause a portion of or the entire bridge to collapse.)
- (2) Those bridges with underwater members which cannot be visually evaluated during periods of low flow or examined by feel for condition, integrity and safe load capacity due to excessive water depth or turbidity. These members shall be described, the inspection frequency stated, not to exceed five years, and the inspection procedure specified.
- (3) Those bridges which contain unique or special features requiring additional attention during inspection to ensure the safety of such bridges and the inspection frequency and procedure for inspection of each such feature.
- (4) The date of last inspection of the features designated in paragraphs (e)(1) through (3) of this section and a description of the findings and follow-up actions, if necessary, resulting from the most recent inspection of fracture critical details, underwater members or special features of each so designated bridge.

[36 FR 7851, Apr. 27, 1971. Redesignated at 39 FR 10430, Mar. 20, 1974, as amended at 44 FR 25435, May 1, 1979; 53 FR 32616, Aug. 26, 1988]

§650.305 Frequency of inspections.

- (a) Each bridge is to be inspected at regular intervals not to exceed 2 years in accordance with section 2.3 of the AASHTO Manual.
- (b) Certain types or groups of bridges will require inspection at less than 2-year intervals. The depth and frequency to which bridges are to be inspected will depend on such factors as age, traffic characteristics, state of maintenance, and known deficiencies. The evaluation of these factors will be

the responsibility of the individual in charge of the inspection program.

(c) The maximum inspection interval may be increased for certain types or groups of bridges where past inspection reports and favorable experience and analysis justify the increased interval of inspection. If a State proposes to inspect some bridges at greater than the specified two-year interval, the State shall submit a detailed proposal and supporting data to the Federal Highway Administrator for approval. The maximum time period between inspections shall not exceed four years.

[36 FR 7851, Apr. 27, 1971. Redesignated at 39 FR 10430, Mar. 20, 1974, as amended at 39 FR 29590, Aug. 16, 1974; 53 FR 32616, Aug. 26, 1988; 57 FR 53281, Nov. 9, 1992]

§650.307 Qualifications of personnel.

- (a) The individual in charge of the organizational unit that has been delegated the responsibilities for bridge inspection, reporting, and inventory shall possess the following minimum qualifications:
- (1) Be a registered professional engineer; or
- (2) Be qualified for registration as a professional engineer under the laws of the State; or
- (3) Have a minimum of 10 years experience in bridge inspection assignments in a responsible capacity and have completed a comprehensive training course based on the "Bridge Inspector's Training Manual," which has been developed by a joint Federal-State task force, and subsequent additions to the manual.
- (b) An individual in charge of a bridge inspection team shall possess the following minimum qualifications:
- (1) Have the qualifications specified in paragraph (a) of this section; or

²The "Bridge Inspector's Training Manual" may be purchased from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

³The following publications are supplements to the "Bridge Inspector's Training Manual": "Bridge Inspector's Manual for Movable Bridges." 1977, GPO Stock No. 050–002–00103–5; "Culvert Inspector's Training Manual," July 1986, GPO Stock No. 050–001–0030–7; and "Inspection of Fracture Critical Bridge Members," 1986, GPO Stock No. 050–001–00302–3.